

FAST SET EPOXY - HARDENER

Page: 1

Compilation date: 27/10/2020

Revision No: 12

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FAST SET EPOXY - HARDENER

Product code: 301603

Synonyms: GPM888

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Cedesa Ltd

	Chater Lea Buildings	
Icknield Way		
	Letchworth	
	Hertfordshire	
	SG6 1WT	
	UK	
Tel:	+44 (0) 1462 480764	
Fax:	+44 (0) 1462 679324	
Email:	mike.joyce@cedesa.co.uk	

1.4. Emergency telephone number

Emergency tel: +44 (0) 1462 480764

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1B: H317 Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. 2.2. Label elements: Label elements: UFI: 7Y8X-3UMC-E007-82XT Hazard statements: H315: Causes skin irritation. H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark

FAST SET EPOXY - HARDENER



	▼
Signal words:	Warning
Precautionary statements:	P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264: Wash exposed skin thoroughly after handling.
	P273: Avoid release to the environment.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352: IF ON SKIN: Wash with plenty of water.
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P337+P313: If eye irritation persists: Get medical advice/attention.
	P332+P313: If skin irritation occurs: Get medical advice/attention.
	P362+P364: Take off contaminated clothing and wash it before reuse.
	P501: Dispose of contents and container to hazardous or special waste collection point,
	in accordance with local, regional, national and/or international regulation.
Haz. ingredients (label):	POLY[OXY(METHYL-1,2-ETANEDIYL)], A-HYDRO-W-HYDROXY-,ETHER WITH 2,2-BIS
	(HYDROXYMETHYL)-1,3-PROPANEDIOL(4:1), 2-HYDROXY-3-MERCAPTOPROPYL
	ETHER; 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

POLY[OXY(METHYL-1,2-ETHANEDIYL)], ALPHA-HYDRO-OMEGA-HYDROXY-,ETHER WITH 2,2-BIS (HYDROXYMETHYL)-1,3-PROPANEDIOL(4:1), 2-HYDROXY-3-MERCAPTOPROPYL ETHER - REACH registered number(s): 01-2120118957-46-0000

EINECS	CAS	PBT / WEL	CLP Classification	Percent
615-735-8	72244-98-5	-	Skin Sens. 1B: H317; Aquatic Chronic	70-90%
			3: H412	

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

202-013-9	90-72-2	-	Acute Tox. 4: H302; Eye Irrit. 2: H319;	5-10%	ĺ
			Skin Irrit. 2: H315		Ĺ

Contains: POLY[OXY(METHYL-1,2-ETHANEDIYL)], ALPHA-HYDRO-OMEGA-HYDROXY-,ETHER

WITH 2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL(4:1), 2-HYDROXY-3-

MERCAPTOPROPYL ETHER

Page: 2

FAST SET EPOXY - HARDENER

Page: 3

Section 4: First aid measures 4.1. Description of first aid measures Skin contact: Wash immediately with plenty of soap and water. Eye contact: Bathe the eye with running water for 15 minutes. Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor. 4.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be mild irritation at the site of contact. Eye contact: There may be irritation and redness. Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting. Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 4.3. Indication of any immediate medical attention and special treatment needed Immediate / special treatment: Eye bathing equipment should be available on the premises. Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. 5.2. Special hazards arising from the substance or mixture Exposure hazards: In combustion emits toxic fumes. 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

FAST SET EPOXY - HARDENER

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State: Liquid
- Colour: Yellow

Odour: Characteristic odour

Flash point°C: >93

Relative density: 1.13

9.2. Other information

Other information: No data available.

FAST SET EPOXY - HARDENER

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

ORL	RAT	LD50	1200	mg/kg
SKN	RAT	LD50	1280	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

- Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.
- Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

FAST SET EPOXY - HARDENER

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Disposal of packaging:
 Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

 NB:
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No		
	2015/830.		
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.		
	H315: Causes skin irritation.		

FAST SET EPOXY - HARDENER

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.